

Innovato 5 Collection Acoustical SPC Click

Size: 9" x 48", 7.25" x 48"

Wear Layer: 20 mil

Texture: Deep Registered Embossment


Thickness: 5 mm (IXPE 1 mm attached Underlayment)

15-year Commercial Warranty when installed per EndureFloors guidelines


ArmourGuard Microbead Technology ensures for extreme scratch resistance

Floorscore certification, contributing to a healthy IAQ


Commercial Grade Waterproof Flooring




Natural White Oak



Logan Bamboo



Catalina Grey



Stadium Oak



Glazed Hickory



Forest Dark



Crystal Oak



Opera House Oak



Packaging Data

Sq. Ft. /Carton	57
Cartons /Pallet	48
Sq. Ft. /Pallet	1152



Installation and Maintenance Guidelines

provided by EndureFloors

Description	Results
ASTM F1700 -(ASTMF2055, ASTM F386, ASTM F410, ASTM F2055, ASTM F1914, ASTM F137, ASTM F2199, ASTM F925, ASTM F2199, ASTM F1515, ASTM F1514, Certificate of Compliance)	Pass
ANSI A.137 Dynamic Co-efficient of Friction	Average DCOF .44
ASTM E648 Critical Radiant Flux of Floor Covering Systems	Meets or exceeds Class 1 rating as specified in NFPA Life Safety Code 101 and IBC 804.2 Classification
ASTM E662 Smoke Density	This sample passes the requirements of 450 or less
ASTM F137 Flexibility of Resilient Flooring Materials	Passes 6mm Mandrel
ASTM F925-Resistant to Chemicals	Pass
ASTM F1514 Measuring Heat Stability-(7 Days)	Test requirements of < 8.0 Delta E were met by the tested samples
ASTM F1515-Measuring Light Stability of Flooring by color change	Test requirements of < 8.0 Delta E were met by the tested samples
ASTM F1914-(Short Term Indentation)	Residual Indentation at 40 lbs-0.015 Inch (7.78%)
ASTM F2199-(Dimensional Stability after exposure to heat)	Length--0.008 Inch per 12 inches (-0.07%) Width-0.013 Inch per 12 inches (-0.11%)
ASTM F2055-(Size, Tolerance)	.016 in/lin ft
ASTM F410-Thickness/Wear Layer	Requirement: Commercial .02, Test Result: .011 inch/.26mm
Certificate of Compliance	Requirement: Max 1/3 of flat surface area/Test Result: Pass
ASTM E90&492 Acoustical Tests	STC61, IIC54, HIIC63



2209 Executive Dr. Garland, TX 75041 866-631-2221

www.endurematerials.com