

Sound Solution Acoustic Underlayment with Vapor Bloc

Premium Acoustical underlayment featuring self-sealing lip & tape system

Size: SSVB450 6' x 75' (450 SF) Sold by the roll

SSVB4900P 3' x 33'4" (100 SF) Sold by palletized box

Material: Frothed Polyurethane Foam with tri-extruded vapor barrier

Density: 20 lbs/CU FT

Thickness: 2.16mm (0.085")

Anti-microbial Protection

Installation: Install for floating or nail-down methods with film side up.

Third-party tested and certified as a low VOC interior building material.

Assure the best contribution to IAQ



The diagram illustrates the product specifications for two roll sizes. On the left, a large roll is shown with a height dimension of 6'. Next to it is a smaller roll with a diameter dimension of 11". On the right, a medium roll is shown with a height dimension of 3' and a diameter dimension of 7". Below the 11" roll is a red box containing 'ROLL SPECIFICATIONS' for the 6' x 75' roll. Below the 7" roll is another red box containing 'ROLL SPECIFICATIONS' for the 3' x 33'4" roll. At the bottom center, a palletized box is shown with the text '49 Rolls Per Palletized Box' below it.

ROLL SPECIFICATIONS

Roll Size
6' x 75' Roll (450ft²)

Roll Weight
74lbs (33.57kg)

Core Size
4" (10.16cm) ID Core

Quantity
Rolls sold individually

ROLL SPECIFICATIONS

Roll Size
3' x 33'4" Roll (100ft²)

Roll Weight
16.3lbs (7.39kg)

Box Weight
848lbs (384.65kg)

Core Size
No Core

Quantity
49 Rolls Per Palletized Box



Planet-Approved. Engineered to Last.™

endurematerials.com 866-631-2221